



Digital binocular microscope, 1000x, integrated 3.2 MP camera, rechargeable, N-PLAN objectives

Observation Method - Transmitted Light	Brightfield	Yes
	Simple polarized light	As optional

Main Body	Type	Upright
	Construction material	Aluminum die-cast

Head	Type	Binocular (Siedentopf)
	Inclination	30°
	360° rotating	Yes
	Interpupillary distance (mm)	48-75
	Dioptric adjustment	On left tube
	Fixing screw for eyepieces	Yes
	Tube inner diameter (mm)	23

Eyepieces	Field number (mm)	18
	Magnification	10x
	Pointer	As optional
	Micrometric scale	As optional
	Diameter of micrometer glass (mm)	20

Nosepiece	Positions	Quadruple
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS

Objectives	Optical system	160
	Anti-fungus treatment	Yes
	Parfocal distance (mm)	45
	Standard magnifications	40x-1000x
	Type	N-PLAN
	Objectives included	4x/0.10, W.D. 15.2 mm
		10x/0.25, W.D. 5.5 mm
40x/0.65, W.D. 0.45 mm		
100x/1.25 (Oil/Water), W.D. 0.13 mm		

Stage	Type	Double layer
	Dimensions (mm)	125x116
	Moving mechanism	Rack and pinion
	Moving range (mm)	70x30
	Material	Anti-scratch painting
	Specimen holder	Yes
	Slide number	1
	X-Y Vernier scale	Yes
	Vernier scale accuracy (mm)	0.1

Condenser - Single Position	Type	Abbe
	Numerical aperture (N.A.)	1.25
	Diaphragms	Iris
	Centrable	Pre-centered
	Focusable	By rotation
Focusing System	Type	Coaxial coarse & fine
	Coarse total travel (mm)	16
	Fine total travel (per single rotation) (mm)	0.4
	Fine graduations	100
	Fine resolution (µm)	4
	Upper stop to prevent contact	Yes
	Adjustable tension	Yes
Transmitted Illumination	Type	X-LED
	X-LED type	X-LED1
	Light source power (W)	1
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	1.5
Power Supply for Transmitted Illumination	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	5 Vdc 500 mA
	LED indicator	Yes
	Rechargeable batteries	Yes
	Battery type	Li-ion (battery pack)
	Working time of batteries (hours)	15
Charging time of batteries (hours)	6	
Accessories Included	Dust cover	Yes
	Immersion oil (10ml)	Yes
	Tension adjustment tool	Yes
	User Manual	Digital version (downloadable)
	USB cable (m)	1.8
	CD-ROM	Yes
Additional Information		Mirror for transmitted light (as optional)
Product Dimensions	Height (mm)	365
	Width (mm)	170
	Depth (mm)	320
Product Weight	(kg)	4
Digital Head	Resolution (MP)	3.2
	Sensor type	CMOS
	Sensor size	1/2.5"
	Sensor aspect ratio	4/3
	Full image size	2048x1536
	Pixel size (µm)	2.2x2.2
	Frame rate	4 fps (2048x1536), 8 fps (1280x1024), 30 fps (640x480)
	S/N ratio (dB)	40
	Dynamic range (dB)	66.5
	Sensitivity (V/lux*s @550nm)	0.53
	Exposure time (s)	15 - 1/1500
	USB type	2.0
	System requirements	Win 7 / Win 8 / Win 10 (32/64 bit)
	Software	OPTIKA Vision Lite