



*Digital video microscope, 400x,
rechargeable, N-PLAN objectives*

Observation Method - Transmitted Light	Brightfield	Yes
	Simple polarized light	As optional
Main Body	Type	Upright
	Construction material	Aluminum die-cast
Head	Type	Monocular
	Inclination	30°
	360° rotating	Yes
	Fixing screw for eyepieces	Yes
	Tube inner diameter (mm)	23
Eyepieces	Field number (mm)	18
	Magnification	10x
	Pointer	As optional
	Micrometric scale	As optional
	Diameter of micrometer glass (mm)	20
	High eyepoint (for glass wearers)	Yes
Nosepiece	Positions	Quadruple
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS
Objectives	Optical system	160
	Anti-fungus treatment	Yes
	Parfocal distance (mm)	45
	Standard magnifications	40x-400x
	Type	N-PLAN
		4x/0.10, W.D. 15.2 mm
		10x/0.25, W.D. 5.5 mm
		40x/0.65, W.D. 0.45 mm

Stage	Type	Fixed
	Dimensions (mm)	130x120
	Moving mechanism	As optional
	Material	Anti-scratch painting
	Specimen clips	Yes
	Slide number	1

Condenser - Single Position	Type	Fixed
	Numerical aperture (N.A.)	0.65
	Diaphragms	Iris
	Centrable	Pre-centered

Focusing System	Type	Coaxial coarse & fine
	Coarse total travel (mm)	16
	Fine total travel (per single rotation) (mm)	0,4
	Fine graduations	100
	Fine resolution (µm)	4
	Upper stop to prevent contact	Yes
	Adjustable tension	Yes

Transmitted Illumination	Type	X-LED
	X-LED type	X-LED1
	Light source power (W)	1
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	1,5

Power Supply for Transmitted Illumination	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	5 Vdc 500 mA
	LED indicator	Yes
	Rechargeable batteries	Yes
	Battery type	Li-ion (battery pack)
	Working time of batteries (hours)	15
Charging time of batteries (hours)	6	

Accessories Included	Dust cover	Yes
	Tension adjustment tool	Yes
	User Manual	Digital version (downloadable)

Additional Information		Mirror for transmitted light (as optional)
-------------------------------	--	--

Product Dimensions	Height (mm)	410
	Width (mm)	170
	Depth (mm)	320

Product Weight	(kg)	4
-----------------------	------	---

DIGITAL HEAD WITH MONITOR

General specifications	SD Card Still image capture	Yes
	SD Card Video recording	Yes
	Dimensions (mm)	180 x 150 x 90
	Weight (kg)	0.360

Sensor	Camera resolution (n° of pixels: W x H)	1920x1080
	Camera resolution (MP)	2
	Frame rate full resolution (fps)	30@1920x1080
	Color / Monochrome	Color
	Sensor Size	1/2.8"
	Sensor Technology	CMOS
	Sensor Type	MICRON CMOS
	Image Format	16/9
	Pixel Size (µm)	2.9x2.9
	Acquisition technology	Rolling shutter
	Exposure time	0- 33333 µs
	IR filter	Yes
	IR filter range (nm)	680

Monitor	Display size	7"
	Display resolution	1024x600

System Power Supply	Type	External
	Connector	Jack, 2.1 mm
	Power plug type	Multiplug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60Hz
	Output voltage	12 Vdc, 1000 mA
	LED indicator	Yes

Available Software	Camera SW	S-Viewer
---------------------------	-----------	----------

System accessories	SD card	4GB
	USB SD card reader	Yes