## KERN OBE 132



Elegant, dynamic and impressive - the all-round compound microscope for schools, training and laboratories



Category	
Brand	Optics
Product categoriy	Microscope
Product group	Compound microscope
Product family	OBE-13
Approval	
Approval	
CE mark	✓
Construction	
Dimension (W×D×H)	360×150×320 mm
Optical system	Finite
Tube type	Butterfly
Tube type	Binocular
Tube angle of inclination	30°
Lens quality	achromatic
Standard objectives	4× 10× 40× 100×
Nosepiece screw-in locations	4
Diopter adjustment	one-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5
Contrasting methods	Bright field Darkfield (optional) Polarisation (optional)
Interpupillary distance [Max]	75 mm
Interpupillary distance [Min]	48 mm
Colour temperature	6000 K

Ocular	
Ocular field width	HWF
Eye point	High Eye Point
Ocular magnifications	10 x
Ocular visual field	18 mm
Ocular diameter	23,2 mm
Focussing	
Fine drive minimum	0,002 mm
Torque regulation	1
Field of view [Min]	0,18 mm
Field of view [Max]	4,5 mm
Focusing mechanism	coaxial coarse and fine drive
Illumination	
Illumination type incident light	none
Illumination intensity transmitted light	3 W
Illumination type transmitted light	LED
Illuminance	Transmitted light
Illumination dimmable	Transmitted light
Aperture diaphragm	1
Filter possible	1
	•
Dower Supply	
Power Supply	
Power Supply Input voltage power supply / power [Max]	100 V - 240 V AC 50/60 Hz 0,3 A
Input voltage power supply /	100 V - 240 V AC 50/60
Input voltage power supply / power [Max]	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter
Input voltage power supply / power [Max] Input voltage device / power [Max]	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter Power supply unit
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter Power supply unit EURO
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter Power supply unit EURO AUS UK US
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter Power supply unit EURO AUS UK
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter Power supply unit EURO AUS UK US
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter Power supply unit EURO AUS UK US
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter Power supply unit EURO AUS UK US CH
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min]	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter Power supply unit EURO AUS UK US CH -5 °C
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min] Storage temperature [Max]	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter Power supply unit EURO AUS UK US CH -5 °C
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min] Storage temperature [Max] Packing & Shipping	-5 °C 40 °C
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Cenvironmental conditions Storage temperature [Min] Storage temperature [Max] Packing & Shipping Readability force [d] (N)	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter Power supply unit EURO AUS UK US CH -5 °C 40 °C

## KERN OBE 132



Elegant, dynamic and impressive - the all-round compound microscope for schools, training and laboratories

Shipping method	Parcel service
Net weight approx.	4,6 kg
Gross weight approx.	6 kg
Shipping weight	7,1 kg

## Objective

Objectives - Details	Objective Achromatic 10 x / 0,25 anti-fungus Objective Achromatic 100 x / 1,25 oil, spring, anti-fungus Objective Achromatic 4 x / 0,1 anti-fungus Objective Achromatic 40 x / 0,65 spring, anti- fungus

## Pictograms

STANDARD



OPTION

